

Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234

E-mail: saleshelp@tripplite.com

Model #: TLP1210SATG

12 outlet, 10-ft cord, 3600 joules, 2-line coax, 1-line RJ11/RJ45 combo protection Eco Home/Business Theater Surge Suppressor



Highlights

- Want to save \$40/year on your energy bill? Learn how.
- Auto/manual switch offers green energy savings or standard protection
- Unique Netbook Switch allows user to select wattage
- 12 outlets / 10-ft cord
- 3600 joule rating
- 2-line digital gold coax connectors
- 1-line tel/modem/network (100BaseT, high-speed) surge protection
- \$250,000 Ultimate Lifetime Insurance (USA and Canada only)

Description

Want to save \$40 per year on your energy bill? Learn how. The TLP1210SATG offers reliable, green surge technology that protects your A/V installations, the environment and your wallet. The TLP1210SATG offers a unique Netbook switch that allows users to select wattage, so these are the only green surge suppressors compatible with all PCs, Notebooks and Netbooks. Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals. The TLP1210SATG offers 3600 joules of advanced surge protection for all A/V components. You can see and hear the difference: sharper, crisper video; deeper, fuller audio; longer component life spans. Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 12 outlets (with transformer spacing and sliding safety covers), 2-line coaxial protection and 1-line tel/modem/Ethernet (100BaseT, high-speed) protection safeguard an entire home/business theater system. Includes two diagnostic LEDs and four status LED indicators, color-coordinated holographic outlet/plug labels, 10-ft. cord with a right-angle plug, 6-ft. coaxial cable and 6-ft. network cable. \$250,000 Ultimate Lifetime Insurance coverage (USA and Canada only).

Applications

• Perfect for small-to-medium home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- TLP1210SATG Eco Home/Business Theater Surge Suppressor
- 6-ft gold coax cable
- 6-ft network cable
- Instruction manual with warranty information

Features

- Energy-saving outlet configuration reduces energy waste (phantom loads) by cutting AC power to unused peripherals
- Green Outlet Array; "Master" outlet controls power flow for 1 primary and up to 8 peripheral components. "Power Save" outlets cut AC power to 8 connected components when not in use perfect for non-essential components that do not save settings like DVD players, gaming consoles, amplifiers and speaker systems. "Always On" outlets provide continuous power to 3 critical devices that save settings like DVRs and recorders (TiVo), cable and satellite boxes
- User-adjustable wattage control switch allows for high-wattage (over 25W) and low-wattage (over 15W) components to serve as Master device
- Auto/Manual Switch allows users to switch between green (auto) power-save mode and standard (manual) surge protection
- 3600 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 12 widely spaced surge-protected NEMA 5-15R AC outlets safeguard and entire home/business theater system while accommodating up to 8 large transformers

- Sliding safety covers protect against accidental contact
- 2 sets of surge-protected Type F gold coaxial connectors safeguard components on cable, satellite and antenna line
- 1-line tel/modem/Ethernet (100BaseT, high-speed) surge protection safeguards personal video recorders (PVRs) on a single DSS or Ethernet line.
- 10-ft. cord with right-angle NEMA 5-15P plug
- 2 diagnostic LEDs alert user to protection and grounded status and 4 status LEDs indicates when AC power is present
- Keyhole slots provide convenient wall or cabinet mounting
- \$250,000 Ultimate Lifetime Insurance coverage (USA and Canada only)

Specifications

OVERVIEW		
Intended Application	Green (Energy-Saving)	
OUTPUT		
Output Volt Amp Capacity (VA)	15	
Output Watt Capacity (watts)	1800	
Frequency compatibility	60 Hz	
Outlet quantity / type	12 NEMA 5-15R	
Outlet Type	12 NEMA 5-15R	
Transformer accommodation	Accommodates 8 transformers	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input plug features	Space-saving right-angle input plug	
Input cord length (ft.)	10	
Input cord length (m)	3	
Input cord gauge, type	14 gauge, SJT	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	228000	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	3600	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	150	
UL1449 let through rating	330, 400, 400	
EMI / RFI filtering	Up to 40 dB	
DATALINE SURGE SUPPRESS	ON	

Shipping weight (lbs) 2.76 Shipping weight (kg) 1.25 Unit Dimensions (HWD/Im) 1.54 x 4.72 x 11.88 Unit Dimensions (HWD/Im) 3.91 x 11.99 x 30.18 Shipping Dimensions (HWD/Im) 2.05 x 8.66 x 13.39 Shipping Dimensions (HWD/Im) 5.21 x 22.00 x 34.01 Unit weight (lbs) 2.55 Unit weight (kg) 1.16 Material of construction Plastic Integrated keyhole mounting Keyhole mounting slots allow desk or wall mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm measurement Keyhole slot center to center measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm SPECIAL FEATURES Power saving auto-shutoff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC suppression) UL1449 3rd Edition (AC suppression) UL-1497A (Communications) UL497A FCC Part 68 (Communications) OUL CUL / CSA (Canada) OUL	Telephone/DSL Protection	Yes	
Datalis of Network (Ethernet) Protection Yes PHYSICAL Shipping welght (lbs) 2.76 Shipping welght (kg) 1.25 Unit Dimensions (HWDim) 1.54 x 4.72 x 11.88 Unit Dimensions (HWDim) 3.91 x 11.99 x 30.18 Shipping Dimensions (HWDim) 2.05 x 8.66 x 13.39 Unit Welght (lbs) 2.55 Unit welght (lbs) 2.56 Unit welght (lbs) 1.16 Matorial of construction Plastic Integrated keyhole mounting slots allow desk or wall mounting slots allow desk or wall mounting slots allow desk or wall mounting slots acrea to content or content measurement Sitip Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm measurement Keyhole slot center to center measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm Keynole Plug Yes CECRIFIECATIONS UL1449 3rd Edition (AC Suppress) UL1449 3rd Edition (AC Suppress) UL1437 A Edition (AC Suppress) UL1437 A Edition (AC Suppress) UL1437 A Edition (AC Suppress) UL1437 A Communications) FCC Part 68 ECC Part 68	Cable (Coax) Protection	Yes	
Shipping weight (lbs) 2.76 Shipping weight (kg) 1.25 Unit Dimensions (HWD/Im) 1.54 x 4.72 x 11.88 Unit Dimensions (HWD/Im) 2.95 x 8.66 x 13.39 Shipping Dimensions (HWD/Im) 5.21 x 22.00 x 34.01 Unit weight (lbs) 2.55 Unit weight (kg) 1.16 Material of construction Plastic Integrated keyhole mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm measurement Keyhole slot center to center measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm measurement SPECIAL FEATURES Green & high efficiency forest aving auto-shutoff ECO outlets features Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd EDITION UL1363 (Power Tap) UL1363 UL497A (Communications) UL497A FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) UL161EE E587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty		2 line	
Shipping weight (kg) 1.25 Unit Dimensions (HWD/in) 1.54 x 4.72 x 11.88 Unit Dimensions (HWD/in) 3.91 x 11.99 x 30.18 Shipping Dimensions (HWD/in) 2.05 x 8.66 x 13.39 (HWD/in) 5.21 x 22.00 x 34.01 Unit weight (kg) 2.55 Unit weight (kg) 1.16 Material of construction Plastic Integrated keyhole mounting Keyhole mounting slots allow desk or wall mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Distance between horizontal tabs = 15.2mm; Distance between vertical tabs = 73.5mm measurement Distance between horizontal tabs = 15.2mm; Distance between vertical tabs = 73.5mm measurement SPECIAL FEATURES Green & high efficiency features Power saving auto-shutoff ECO outlets features Power Tap) UL1.449 3rd Edition (AC Suppression) UL1497A FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) Lifetime limited warranty Product Warranty Period Lifetime limited warranty Product Warranty Period Lifetime limited warranty	Network (Ethernet) Protection	Yes	
Shipping weight (kg) 1.55 Unit Dimensions (HWD/im) 1.54 x 4.72 x 11.88 Unit Dimensions (HWD/im) 3.91 x 11.99 x 30.18 Shipping Dimensions (HWD/im) 2.05 x 8.66 x 13.39 Shipping Dimensions (HWD/im) 5.21 x 22.00 x 34.01 Unit weight (kb) 2.55 Unit weight (kg) 1.16 Material of construction Plastic Integrated keyhole mounting Keyhole mounting slots allow deak or wall mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm measurement Keyhole slot center to center measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm SPECIAL FEATURES Green & high efficiency Fower saving auto-shuloff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1497 A FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	PHYSICAL		
Unit Dimensions (HWD/in) 1.54 x 4.72 x 11.88 Unit Dimensions (HWD/em) 3.91 x 11.99 x 30.18 Shipping Dimensions (HWD/em) 5.21 x 22.00 x 34.01 (HWD/em) 5.21 x 22.00 x 34.01 (HWD/em) 7.25 Unit weight (tbs) 2.55 Unit weight (tbs) 1.16 Material of construction Plastic Integrated keyhole mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm measurement Republic Strip Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm Percent Features Power saving auto-shutoff ECO outlets (ERTIFICATIONS) UL1449 3rd Edition (AC Suppression) UL1449 3rd EDITION UL1363 UL497A (Communications) UL497A FCC Part 68 (Communications) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warrant Period Lifetime limited warranty	Shipping weight (lbs)	2.76	
Unit Dimensions (HWD/cm) \$1.91 x 11.99 x 30.18 \$1.10.ping Dimensions (HWD/cm) \$2.05 x 8.66 x 13.39 \$1.10.ping Dimensions (HWD/cm) \$2.1 x 22.00 x 34.01 Unit weight (lbs) \$2.55 Unit weight (lbs) \$2.55 Unit weight (kg) \$1.16 Material of construction Flastic Integrated keyhole mounting lates Keyhole mounting slots allow desk or wall mounting lates AC line cord color Black \$1.10 Outlets center to center measurement Keyhole slot center to center measurement Keyhole slot center to center measurement Bistance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm **SPECIAL FEATURES** Green & high efficiency features Power saving auto-shutoff ECO outlets Suppression) UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) FCC Part 68 (Communications) ECC Part 68 (Communications) EXCENDIFICATIONS UL1 CSA (Canada) LUL (CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANNTY Product Warranty Period Lifetime limited warranty	Shipping weight (kg)	1.25	
Shipping Dimensions (HWD/Im) Shipping Dimensions (HWD/Im) 5.21 x 22.00 x 34.01 Unit weight (lbs) 2.55 Unit weight (kg) 1.16 Material of construction Plestic Integrated keyhole mounting labs Keyhole mounting slots allow desk or wall mounting labs AC line cord color Black Style Strip Outlets center to center measurement Keyhole slot center to center measurement Keyhole slot center to center measurement Power saving auto-shutoff ECO outlets Green & high efficiency features Power saving auto-shutoff ECO outlets CERTIFICATIONS UL1343 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 (Power Tap) UL497A (Communications) FCC Part 68 (Communications) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty Lifetime limited warranty Lifetime limited warranty Lifetime limited warranty Expeciations Lifetime limited warranty	Unit Dimensions (HWD/in)	1.54 x 4.72 x 11.88	
Shipping Dimensions	Unit Dimensions (HWD/cm)	3.91 x 11.99 x 30.18	
Unit weight (lbs) 2.55 Unit weight (kg) 1.16 Material of construction Integrated keyhole mounting labs AC line cord color Style Strip Outlets center to center measurement Keyhole slot center to center measurement SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Ves CERTIFICATIONS UL1449 3rd EDITION UL1363 (Power Tap) UL497A FCC Part 68 (Communications) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Integrated keyhole mounting latis and selection in the sel	Shipping Dimensions (HWD/in)	2.05 x 8.66 x 13.39	
Material of construction Material of construction Plastic Keyhole mounting slots allow desk or wall mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Keyhole slot center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty Product Warranty Period Lifetime limited warranty	Shipping Dimensions (HWD/cm)	5.21 x 22.00 x 34.01	
Material of construction Plastic Integrated keyhole mounting tabs AC line cord color Black Style Strip Outlets center to center measurement Keyhole slot center to center measurement SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 UL497A (Communications) FCC Part 68 (Communications) UL497A FCC Part 68 (Communications) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	Unit weight (lbs)	2.55	
Integrated keyhole mounting labs AC line cord color Black Style Strip Outlets center to center measurement Keyhole slot center to center measurement SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Ves CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL497A (Communications) FCC Part 68 (Communications) CUL / CSA (Canada) Lifetime limited warranty Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Itielime limited warranty Extered Strip Strip	Unit weight (kg)	1.16	
AC line cord color Black Style Strip Outlets center to center measurement Keyhole slot center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) FCC Part 68 (Communications) EXECUTE 68 (Communications) EXECUTE 68 (Communications) EXECUTE 68 CUL / CSA (Canada) EXECUTE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	Material of construction	Plastic	
Style Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm Keyhole slot center to center measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm SPECIAL FEATURES Green & high efficiency features Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) FCC Part 68 (Communications) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty Lifetime limited warranty	Integrated keyhole mounting tabs	Keyhole mounting slots allow desk or wall mounting	
Outlets center to center measurement Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm Measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm Power saving auto-shutoff ECO outlets Green & high efficiency features Power saving auto-shutoff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) UL497A FCC Part 68 (Communications) UL497A CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty Lifetime limited warranty	AC line cord color	Black	
Measurement Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm SPECIAL FEATURES Green & high efficiency features Power saving auto-shutoff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1449 3rd EDITION UL1363 (Power Tap) UL363 UL497A (Communications) UL497A FCC Part 68 (Communications) FCC Part 68 (Communications) cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	Style	Strip	
measurement SPECIAL FEATURES Green & high efficiency features Power saving auto-shutoff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) UL497A FCC Part 68 (Communications) FCC Part 68 (Communications) cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty		Distance between standard outlets = 25.4mm; Distance between transformer outlets = 57mm	
Green & high efficiency features Power saving auto-shutoff ECO outlets Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL1363 UL497A (Communications) UL497A FCC Part 68 (Communications) FCC Part 68 cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty		Distance between horizontal tabs = 152mm; Distance between vertical tabs = 73.5mm	
Right-Angle Plug Yes CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL497A (Communications) FCC Part 68 (Communications) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	SPECIAL FEATURES		
CERTIFICATIONS UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL497A (Communications) FCC Part 68 (Communications) CUL / CSA (Canada) Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty		Power saving auto-shutoff ECO outlets	
UL1449 3rd Edition (AC Suppression) UL1363 (Power Tap) UL497A (Communications) UL497A FCC Part 68 (Communications) CUL / CSA (Canada) Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	Right-Angle Plug	Yes	
Suppression) UL1363 (Power Tap) UL497A (Communications) UL497A FCC Part 68 (Communications) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	CERTIFICATIONS		
UL497A (Communications) FCC Part 68 (Communications) CUL / CSA (Canada) CUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty		UL1449 3rd EDITION	
FCC Part 68 (Communications) cUL / CSA (Canada) cUL Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	UL1363 (Power Tap)	UL1363	
(Communications) cUL / CSA (Canada) Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	UL497A (Communications)	UL497A	
Approvals Exceeds IEEE 587 category A&B specifications WARRANTY Product Warranty Period Lifetime limited warranty	FCC Part 68 (Communications)	FCC Part 68	
WARRANTY Product Warranty Period Lifetime limited warranty	cUL / CSA (Canada)	cUL	
Product Warranty Period Lifetime limited warranty	Approvals	Exceeds IEEE 587 category A&B specifications	
Product Warranty Period (Worldwide) Lifetime limited warranty	WARRANTY		
	Product Warranty Period (Worldwide)	Lifetime limited warranty	

Connected Equipment Insurance (U.S., Canada & Puerto Rico)

\$250,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=4493.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.