

LV Series Low Voltage Switches

LOW VOLTAGE WALL SWITCH

TITLE
24
COMPLIANCE

PROJECT INFORMATION

Project Name _____

Catalog No. _____

Date _____



LVSM1NP

LVSM1PL

Our Low Voltage Wall Switches are designed for virtually any area. The soft contours of its architecturally-pleasing design fit easily into any décor. Momentary version switches are available and feature multiple button configurations making them the perfect switch solution for low voltage occupancy sensors, daylighting controls and networked lighting control panels.

PRODUCT FEATURES

- Attractive, architecturally pleasing design
- Momentary button action
- 1-4 buttons with or without LED
- Mounts to standard single-gang box
- California Title 24 compliant
- Five-year limited warranty
- Low voltage device: 24 Vdc

General Specifications

Electrical Ratings	Each switch: 100mA @ 30VDC Max Each pilot LED: 18-30VDC, internal 2.2kohm, ½ Watt resistor
Configurations	1 - 4 buttons, with or without pilot LED Momentary
Operating environment	Indoor use only Operating temperature: 32° to 122°F (0° to 50°C) Relative humidity (non-condensing): 10%-90%
Construction	Housing – Rugged, high-impact, injection-molded plastic Color-coded leads
Dimensions	1.88"W x 4.25"H x 1.56"D (47.75mm x 107.95mm x 39.63mm)
Weight	3.0 oz [85.0 g]
Color	White, Ivory, Light Almond, Gray
Mounting	Single-gang NEMA-style switch box (average switch box) Decorator-style wall plate not included
Warranty	Five-year limited

Ordering Information

LVS	M	1-4	PL w/ Pilot LEDs NP No Pilot	WH White IV Ivory LA Light Almond G Gray
SWITCH MODEL	SWITCH TYPE	NUMBER OF BUTTONS	PILOT	COLOR
LVS	M Momentary	1-4		

Latching button versions are available for special applications, consult factory.



HUBBELL
Control Solutions